



TECHNICAL SPECIFICATION :

| | |
|--|--------------------------|
| Model | DWL 80E |
| Type | Pocket-Size |
| Measurement range (Single Axis) | 0° ~ 90°; 4 x 90° (360°) |
| Measurement range (Dual Axis) | -- |
| Resolution | 0.1° (1.75mm/M) |
| Accuracy | 0.1° |
| (°) Degree, % slope | ● |
| in/Ft, mm/M | -- |
| Dual Axis XY measurement | -- |
| Buzzer sound | -- |
| HOLD function to freeze reading | ● |
| Built in vials | ● |
| Magnet | ● |
| Backlight | -- |
| Alternate Zero (Set any angle to 0) | ● |
| Inverted reading display | -- |
| Auto shut off (Power saving) | ● |
| User self calibration | ● |
| Dimension** L x H x W (mm) | 105 x 55 x 18 |
| Operating temp. | 0° ~ +50° (Celcius) |
| Storage temp. | -10° ~ +60° (Celcius) |
| Waterproof rating | -- |
| Batteries | 2 x CR2032 |

Note : * Product Specification and appearance are subjected to change for product improvement without prior notice.

** Dimension stated in this chart is approximation.

Blank Space - indicate this feature is not available for this model.

Dot "●" - indicate this feature is available for this model.

Applications :




Roof contractor



Solar Modules Installation



Offshore & Shipyard



Home & DIY Work



Satellite Dish Alignment



Steel-Beam Structure Alignment



Window Frame Installation