



Technical Information

AUTOSOL® Acrylic Polish

Product information

- Unique formulation designed to remove scratches from acrylic (Perspex®) surfaces
- It combines specific selected polishing particles with an optimal matrix
- Suitable on almost every clear plastic like Perspex®, Polycarbonate, PMMA etc.
- To remove deeper scratches a pre-treatment with P2000 sandpaper is possible
- Sparingly and easy to apply

Application

Clean the surface to be treated. Put a small amount of the product onto a soft lint free cloth. Apply the product to the scratched surface and polish the surface in a circular motion. Depending on the grade of scratches adjust pressure and polishing time. Remove excessive product thoroughly with a wet sponge or cloth. Dry the surface with a soft lint free cloth.

Note

Do not use on touchscreens. Do not use on printed or coated surfaces.

Technical Data

Form: paste
Colour: white
Odour: odourless

Health and Safety

Safety Data Sheet is available separately.



Additional Information

Art.-No.: 01 001260

tube 75 ml

PU: 12

The information provided in this Technical Information is based on the current status of knowledge and experience and is intended to describe the products with respect to possible applications and safety requirements. This information does not represent a legally binding assurance of specific characteristics. A legally binding assurance of specific characteristics or suitability for the concrete purpose of use cannot be derived from our information. Possible trademarks and existing legislation and stipulations are to be observed by the recipient of our products under his/her own responsibility.