

Electr. Digital Sound Level Meter

- for sound and noise measurements acc. to the international directives whether in industry, craft, or housekeeping
- useful device for air-conditioning, aviation industry, environmental technology
- with self-calibration

- rugged, polyamide housing material
- On/Off button, data memory for 4700 measurements, slow-/fast-button, clock- and calendar indicator
- with tripod mounting screw on the rear side, autom. power off
- large LCD display, 4-digit, with clear reading, battery indicator
- frequency range 31.5 Hz ~ 8.5 KHz, A/C frequency weighting select switch, AC/DC out put
- bar graph indicator with 50 dB scale, 1 dB step, with pre-select of min/max.-value
- microphone 1/2 inch, electret condenser-microphone, with detachable foam ball for outside measuring
- storage temperature -20 °C ~ +70 °C, operation temperature 0 °C ~ +45 °C, DC 6 V input port, AC analog output port
- incl. 4x 1.5 V battery (type AA, art.-no.: 90003), USB data cable, software, with operation manual



foam ball removable









side

Option

- charging by power supply possible (only when using rechargeable batteries)



	 level range dBA / dBC	 dB	 dB	linearity range dB	 mm	 inclusive
641106	40 – 80 / 50 – 100 / 60 – 110 / 80 – 130	0.1	± 1.5	50	220 x 80 x 35	inclusive