


# Spirit Levels „NIVEAU NORM“

- top quality spirit levels with plane surfaces
- rugged light alloy rectangular profile, from up 1500 mm length with extrem solid wallthickness
- with 1x horizontal vial and 1x vertical vial
- barrel-shaped vials with patented SOLID built-in system, permanent fixed and constantly aligned with the profile
- surfaces in stratosilver elocated
- measuring accuracy adjusted by electronical adjustment and at final inspection
- measuring accuracy in normal position  $0.5 \text{ mm/m} = 0.029^\circ$ , with reversal measurement minimum  $0.75 \text{ mm/m} = 0.043^\circ$

art.-no.: 714100 – 714110

- with strong adhesive magnet in the measurement base



plane, rectangular aluminium profile, extruded and warm cured

ART N° 714000 – 714010



without magnets

ART N° 714100 – 714110



with strong adhesive magnet in the measurement base

ART N° 714000 – 714010



ART N° 714100 – 714110



ART N°	mm			
714000	200	50 x 22	X	0.5 mm/m = ±0.029°
714001	300	50 x 22	X	0.5 mm/m = ±0.029°
714002	400	50 x 22	X	0.5 mm/m = ±0.029°
714003	500	50 x 22	X	0.5 mm/m = ±0.029°
714004	600	50 x 22	X	0.5 mm/m = ±0.029°
714005	800	50 x 22	X	0.5 mm/m = ±0.029°
714006	1000	50 x 22	X	0.5 mm/m = ±0.029°
714007	1200	50 x 22	X	0.5 mm/m = ±0.029°
🚚 714008	1500	50 x 22	X	0.5 mm/m = ±0.029°
🚚 714009	1800	50 x 22	X	0.5 mm/m = ±0.029°
🚚 714010	2000	50 x 22	X	0.5 mm/m = ±0.029°
714100	200	50 x 22	✓	0.5 mm/m = ±0.029°
714101	300	50 x 22	✓	0.5 mm/m = ±0.029°
714102	400	50 x 22	✓	0.5 mm/m = ±0.029°
714103	500	50 x 22	✓	0.5 mm/m = ±0.029°
714104	600	50 x 22	✓	0.5 mm/m = ±0.029°
714105	800	50 x 22	✓	0.5 mm/m = ±0.029°
714106	1000	50 x 22	✓	0.5 mm/m = ±0.029°
714107	1200	50 x 22	✓	0.5 mm/m = ±0.029°
🚚 714108	1500	50 x 22	✓	0.5 mm/m = ±0.029°
🚚 714109	1800	50 x 22	✓	0.5 mm/m = ±0.029°
🚚 714110	2000	50 x 22	✓	0.5 mm/m = ±0.029°