

Technical Sprays

Surface and anti-corrosion coating

Isolation Spray

Transparent insulating and finishing varnish based on acrylic

WEICON Isolation Spray is a transparent insulating and finishing varnish based on acrylic resin. It forms a flexible and resistant layer, which shows excellent adhesion to metal, glass, plastic or wood. It is resistant to UV radiation, acids, oils and lyes. It is moisture- and weather-resistant and stands out particularly due to its high dielectric strength. The spray protects against moisture as well as different vapours. It can be used as protective coating for circuit boards, on electrical connections, switches, switchboards, electronic components and coils, as universal sealant in electrical engineering or for the repair of insulations on electric motors, windings and frames.

Technische Daten

Base		modified acrylic resin
Odour		solvent
Specific properties		high dielectric strength, material-compatible
Silicone-free		yes
Consumption	per 1.5 crosswise application	~ 2 m²
Dust-dry		15 min.
Cross cutting	DIN 53151/ISO 2409	cross cut value 0-1 on steel
Density		0,848 g/cm ³
Dielectric strength	DIN EN 60243	67,8 kV/mm
Solid content		50 %
spec. surface resistance		7,59
Thermal conductivity	20 °C DIN EN ISO 821	0,215 W/m·K
Temperature resistance		-40 (-40 °F) to +120 (+248 °F)
Shelf life		24 mon.

Processing

Clean and degrease surfaces with WEICON Surface Cleaner. Surfaces should be dry and free from dust and grease. Shake can before use, until the mixing pea is clearly audible. Apply the spray at room temperature (approx. +20 °C) evenly from a distance of approx. 25 cm.

Storage

Pressurized container. Protect from direct sunlight and temperatures above +50 °C.

Instructions for use

When using WEICON products, the physical, safety-related, toxicological and ecological data and regulations in our EC safety data sheets (www.weicon.com) must be observed.

Available sizes



The specifications and recommendations given in this technical data sheet must not be seen as guaranteed product characteristics. They are based on our laboratory tests and on practical experience. Since individual application conditions are beyond our knowledge, control our products. However, own adequate laboratory and practical tests to find out if the product in question meets the requested properties are recommended. A claim cannot be derived from them. The user bears the user bears they responsibility for non-appropriate or other than specified applications.

Italy phone +39 (0) 010 2924 871

WEICON Romania SRL phone +40 (0) 3 65 730 763

WEICON SA (Pty) Ltd South Africa phone +27 (0) 21 709 0088 info@weicon.co.za

WEICON South East Asia Pte Ltd ne (+65) 6710 7671

WEICON Kimya Sanayi Tic. Ltd. Sti. Turkey phone +90 (0) 212 465 33 65