
SILVER-LINE

Image/Video Borescope Console • IP54 with 3.5" TFT colour monitor, with connection for all our hoses

- top model for varied industry purposes,
 e.g. automotive-, machinery-, pipeline-, shipbuilding-,
 aircraft-, turbine-, wind power industry, and many more
- for quick, visual inspection and documentation, useful in hard to reach places
- with 3 adjustable LED's at the hose-end
- with USB 2.0, TV output (PAL), reset, mini-USB and micro SD slot
- spray water proof console, acc. to DIN 40050 / IEC 60529
- sturdy industry quality, housing with rubber cover, M6 thread insert
- 3.5 inch TFT colour monitor, monitor resolution 640x480 pixel
- photo taking (JPEG 1600x1200) and video recording (AVI)
- with zoom button (x2/x3/x4) and image freeze
- 180° frame rotation and mirror image
- 7 selectable languages, DE/EN/FR/ES/RU/JP/CN
- ON/OFF button, date/time function, power saving mode, battery status
- build-in flashlight (level-1/-2/-3)
- build-in rechargeable Li-ion battery
- incl. 4 GB memory SD card, USB power cable (USB/mini-USB), 240 V USB charger, AV cable, bracket with M6 thread, with operation manual, in a carry bag







table stand with M6 thread

LED light (3 levels)



LED light

tube threaded connection

TV connection mini USB connection



memory card (4 GB)







USB charger



rear with rubberized housing protection



rear without rubberized housing protection



USB charger cable





Example: brake discs control















0

90

ART NO
Photo (JPG)
Video (AVI)

620003

1600 x 1200

640 x 480

145 x 95 x 37

0.290

Accessories for Borescopes

Image/Video Borescope Hoses • IP67 endoscope hoses with matching threaded connection suitable for our model console (art.-no. 620003)

- · different hoses available
- oil-, water- and coolant proof, acc. to DIN 40050 / IEC 60529
- sturdy industry quality, flexible and semi-ridgid design
- camera resolution 300.000 pixel
- perfect image recognition in the depth of field
- lenses with bright, white LED's
- 3 times adjustable LED light, console setting
- with operation manual, in a carton box





hose ø 3.7 mm or ø 4.5 mm, with 0° lens

above: hose ø 9.0 mm, with 0° and 90° lens



below: hose Ø 3.7 mm, with 0° lens



rubberized grip for secure grip, only at viewing direction 0° and 90°



hose ø 9.0 mm, with 0° and 90° lens

5 D.T.B. 10	hose	field of view	hose-Ø	quantity	hose	type	
ART NO	mm	0	mm	LED	flexible	semi rigid	KG
620050	1000	0	3.7	6	✓	X	0.050
620051	3000	0	3.7	6	✓	X	0.125
620052	5000	0	3.7	6	✓	X	0.225
620055	1000	0	4.5	6	X	✓	0.065
620056	3000	0	4.5	6	X	✓	0.115
620057	5000	0	4.5	6	X	✓	0.300
620060	1000	0 / 90	9.0	4/2	X	✓	0.210
620061	3000	0 / 90	9.0	4/2	X	✓	0.570
620062	5000	0 / 90	9.0	4/2	X	✓	1.020

2

9

_

 ∞

0

10